



DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL
FICHA TÉCNICA

DISCO DURO EXTERNO

- **Tamaño:** 1 TB
- **Tipo:** SSD Externo
- **Conexión:** Tipo A Usb 3.0
- **Velocidad Lectura Mínima:** 1050MB
- **Velocidad Escritura Mínima:** 1000MB





DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL

FICHA TÉCNICA

COMPUTADORA PERSONAL (PC)

- OEM
- Case SFF
- Windows 10 Pro, 64 bits, Español
- Intel® Core™ i5-11500, 12 MB Cache, 6 Cores, 12 Threads, 2.70 GHz to 4.80 GHz, 65 W
- UDIMM sin ECC de 16 GB (2 X 8 GB) de memoria DDR4 a 3200 MHz.
- 4 ranuras de Memoria (con soporte hasta 128GB)
- M.2 2280, 256 GB, PCIe NVMe Gen3 x4, Class 40 SSD
- Unidad de disco óptica DVD+/-RW 8x,
- Teclado Español
- Mouse color negro
- Debe tener TPM 2.0
 - **Periféricos de Entrada y Salida**
 - **Parte Frontal**
 - 1 Puerto USB 3.2 Gen 2
 - 1 Puerto USB 2.0 with PowerShare
 - 1 Puerto USB 2.0
 - 1 Puerto USB 3.2 Gen 2x2 capable Type-C
 - 1 Puerto audio Universal
 - **Parte Trasera**
 - 3 Puertos USB 3.2 Gen 1
 - 1 Puerto USB 3.2 Gen 2
 - 2 Puertos USB 2.0
 - 1 Puerto audio re-tasking Line out/Line in
 - 2 Puertos DisplayPuerto 1.4
 - 1 Puerto Ethernet RJ45
 - 1 Puerto HDMI
 - 2 Puertos PS/2





DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL

FICHA TÉCNICA

MONITOR

- 24 Pulgadas
- LED con Tecnología BackLight"
- Resolución 1920 x 1080 at 60 Hz
- 1 DisplayPuerto version 1.2
- 1 HDMI Puerto version 1.4
- 1 VGA Puerto
- 1 USB 3.0 Puerto hacia arriba
- 2 USB 3.0 Puertos Laterales
- 2 USB 2.0 Parte de Abajo
- Tiempo de Respuesta 8ms
- Panel IPS
- Pixeles 0.275 mm x 0.275 mm
- Radio de contraste 1000:1
- Radio de aspect 16:9
- Base Giratoria.





DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL
FICHA TÉCNICA

LAPTOPS DISEÑO

- OEM
- Windows 10 Pro, 64-bit, Español
- 11th Generation Intel® Core™ i7-11800H (8 Core, 24M cache, base 3.2GHz, up to 4.6GHz, vPro)
- 16GB de Memoria DDR4 a 3200MHz (2 x 8GB)
- M.2 512GB PCIe NVMe Class 40 Solid State Drive
- 15.6" Full HD (1920 x 1080 píxeles), IPS-Level
- NVIDIA® GeForce RTX™ 3050Ti Laptop GPU, 4GB GDDR6SD
- Teclado español interno, iluminado
- Tarjeta inalámbrica de doble banda Wi-Fi 6 2X2 (Gig+) y BT 5.2
- Batería (3 celdas) de 53.5 Whr
- Cámara Web HD 720p
- Entrada de audio universal
- 1 USB Type-C
- 2 x USB 3.2
- 1 x USB 2.0
- 1 x HDMI
- 1 x RJ45
- Garantía de 2 años en Piezas y Servicios





DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL

FICHA TÉCNICA

TELÉFONO EJECUTIVO PARA SKYPE FOR BUSINESS

USER INTERFACE FEATURES

- Gesture-based, multitouch-capable touchscreen
- 7" color LCD (1024 x 600 pixel)
- 16:9 aspect ratio Screensaver
- On-screen virtual keyboard
- Voicemail support
- Adjustable base height
- One USB type-A port (2.0 compliant) for media and storage applications
- One USB Type-C port (2.0 compliant) for media and storage applications
- Integrated Bluetooth 4.2
- Integrated Wi-Fi
- Unicode UTF-8 character support
- Normal and dark mode

AUDIO FEATURES

- HD Voice technology delivers lifelike voice quality for each audio path: handset, hands-free speakerphone, and optional headset
- Acoustic Clarity technology providing full duplex conversations, acoustic echo cancellation, and background noise suppression
- TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)
- Frequency response—100 Hz–20 kHz for handset, optional headset, and handsfree speakerphone modes
- Codecs: G.711 (A-law and μ -law), G.729AB, G.722 (HD Voice), G.722.1 iLBC
- Voice Activity Detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment

HEADSET AND HANDSET COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- USB headset support
- Bluetooth headset support





DIRECCIÓN GENERAL DE CONTABILIDAD GUBERNAMENTAL

FICHA TÉCNICA

NETWORK AND PROVISIONING

- SIP protocol support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port gigabit Ethernet switch 10/100/1000 Base-TX across LAN and PC ports
- Wi-Fi network connectivity—2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20)-5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)
- Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
- Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN—CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery - Network address translation support for static configuration and “keep-alive”
- SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4 and IPv6
- TCP
- UDP
- DNS-SRV

SECURITY

- 802.1X authentication and EAPOL
- Media encryption via SRTP
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables
- Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)

ENERGIA

- Deben tener su Fuente de Alimentación.

